

Package: Dogoftest (via r-universe)

February 19, 2025

Title Distributed Online Goodness-of-Fit Tests for Distributed Datasets

Date 2025-02-15

Version 0.1

Description Distributed Online Goodness-of-Fit Test can process the distributed datasets. The philosophy of the package is described in Guo G.(2024) <[doi:10.1016/j.apm.2024.115709](https://doi.org/10.1016/j.apm.2024.115709)>.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

Imports stats

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation no

Author Guangbao Guo [aut, cre]
(<<https://orcid.org/0000-0002-4115-6218>>), Di Chang [aut]

Maintainer Guangbao Guo <ggb11111111@163.com>

Depends R (>= 3.5.0)

Date/Publication 2025-02-18 10:00:05 UTC

Repository <https://guangbaog.r-universe.dev>

RemoteUrl <https://github.com/cran/Dogoftest>

RemoteRef HEAD

RemoteSha b0ceed9837c9f0d0a47f80eef5de8f163b2b9123

Contents

cvmgof	2
ksgof	2
qCvMgof	3
simpleCvMgof	4
Index	5

`cvmgof`*Perform the Cramer-von Mises Goodness-of-Fit Test for Normality*

Description

Perform the Cramer-von Mises Goodness-of-Fit Test for Normality

Usage

```
cvmgof(x)
```

Arguments

`x` A numeric vector containing the sample data.

Value

`statistic` The value of the Cramer-von Mises test statistic.
`p.value` The p-value for the test.
`method` A character string describing the test.

Examples

```
# Example usage:
set.seed(123)
x <- rnorm(100) # Generate a sample from a normal distribution
result <- cvmgof(x)
print(result)

# Example with non-normal data:
y <- rexp(100) # Generate a sample from an exponential distribution
result <- cvmgof(y)
print(result)
```

`ksgof`*Perform the Lilliefors (Kolmogorov-Smirnov) Goodness-of-Fit Test for Normality*

Description

Perform the Lilliefors (Kolmogorov-Smirnov) Goodness-of-Fit Test for Normality

Usage

```
ksgof(x)
```

Arguments

x A numeric vector containing the sample data.

Value

statistic The value of the Lilliefors (Kolmogorov-Smirnov) test statistic.
 p.value The p-value for the test.
 method A character string describing the test.

Examples

```
# Example usage:
set.seed(123)
x <- rnorm(100) # Generate a sample from a normal distribution
result <- ksgof(x)
print(result)

# Example with non-normal data:
y <- rexp(100) # Generate a sample from an exponential distribution
result <- ksgof(y)
print(result)
```

qCvMgof *Calculate the Quantile of the Cramer-von Mises Goodness-of-Fit Statistic*

Description

This function calculates the quantile of the Cramer-von Mises goodness-of-fit statistic using the ‘uniroot’ function to find the root of the given function.

Usage

```
qCvMgof(X, p)
```

Arguments

X A numeric vector containing the sample data.
 p A numeric value representing the desired quantile probability.

Value

root The quantile value corresponding to the given probability.

Examples

```
# Example usage:
set.seed(123)
X <- rnorm(100) # Generate a sample from a normal distribution
p <- 0.95      # Desired quantile probability
result <- qCvMgof(X, p)
print(result)
```

`simpleCvMgof`*Perform a Simple Cramer-von Mises Goodness-of-Fit Test*

Description

This function performs a simple Cramer-von Mises goodness-of-fit test to assess whether a given sample comes from a uniform distribution. The test statistic and p-value are calculated based on the sorted sample data.

Usage

```
simpleCvMgof(X)
```

Arguments

`X` A numeric vector containing the sample data.

Value

<code>statistic</code>	The value of the Cramer-von Mises test statistic.
<code>pvalue</code>	The p-value for the test.
<code>statname</code>	The name of the test statistic.

Examples

```
# Example usage:
set.seed(123)
X <- runif(100) # Generate a sample from a uniform distribution
result <- simpleCvMgof(X)
print(result)

# Example with non-uniform data:
Y <- rnorm(100) # Generate a sample from a normal distribution
result <- simpleCvMgof(Y)
print(result)
```

Index

`cvmgof`, 2

`ksgof`, 2

`qCvMgof`, 3

`simpleCvMgof`, 4